

# SKYFALL SERIES LED HIGHBAY LIGHT

## FEATURES:

- Top quality PHILIPS LED Chip
- MEAN WELL Driver
- Wide input voltage : AC100V – 277V
- 2 years warranty
- Less light decay, High brightness & Easy installation
- High quality aluminium, great for heat dissipation
- No UV or IR radiation, Environment friendly
- High power factor to ensure the high energy saving



## TECHNICAL DATA:

| Model                             | SKYFALL I                                         | SKYFALL II                  | SKYFALL III                 |
|-----------------------------------|---------------------------------------------------|-----------------------------|-----------------------------|
| Dimension (light body)            | Dia390*230mm                                      | Dia390*230mm                | Dia390*230mm                |
| Power Supply                      | AC : 100V-277Vac<br>50/60Hz                       | AC : 100V-277Vac<br>50/60Hz | AC : 100V-277Vac<br>50/60Hz |
| Power                             | 100W                                              | 150W                        | 200W                        |
| Light Source                      | PHILIPS LED                                       | PHILIPS LED                 | PHILIPS LED                 |
| LED Quantity                      | 196pcs                                            | 196pcs                      | 238pcs                      |
| Luminous Flux                     | 10,000lm / 11,000lm                               | 15,000lm / 16,500lm         | 20,000lm / 22,000lm         |
| Colour Temperature                | 3500K / 6500K                                     | 3500K / 6500K               | 3500K / 6500K               |
| Beam Angle                        | 45° / 90° / 120°                                  | 45° / 90° / 120°            | 45° / 90° / 120°            |
| Colour Rendering Index (CRI)      | Ra > 80                                           | Ra > 80                     | Ra > 80                     |
| LED Life Span                     | 50,000 Hrs                                        | 50,000 Hrs                  | 50,000 Hrs                  |
| Lumen Maintenance @<br>50,000 Hrs | 70% Lumen Maintenance                             | 70% Lumen Maintenance       | 70% Lumen Maintenance       |
| LED Luminous Efficiency           | > 100lm/W                                         | > 100lm/W                   | > 100lm/W                   |
| Power Factor (PF)                 | > 0.95                                            | > 0.95                      | > 0.95                      |
| Total Harmonic Distortion (THD)   | ≤ 15%                                             | ≤ 15%                       | ≤ 15%                       |
| Ingress Protection(IP)            | IP65                                              | IP65                        | IP65                        |
| Gross Weight (KG)                 | 6.9KG                                             | 6.9KG                       | 6.9KG                       |
| Operating Temperature Range       | -25 °C ~ 50°C                                     | -25 °C ~ 50°C               | -25 °C ~ 50°C               |
| Certificate                       | CE, RoHS, ETL, DLC, SAA                           |                             |                             |
| Application                       | Eateries, Retail, Hallways, Storage Rooms & Halls |                             |                             |

Note: Specifications are subject to change without prior notice



## Super Spruce Energy S/B (1112532-A)

No. 2 Block B, Lot 756, Jalan Subang 3, Taman Industrial Sg Penaga, 47610 Subang Jaya, Selangor Darul  
Ehsan Tel: 03 8081 1326 / 7326 Fax: 03 8081 5326 Email: sales@onirii.com.my